

Heat demand mapping and the utilization of district heating in energy systems with a high share of renewables: Case study for the city of Osijek

T.Novosel, M. Ban, I. Bačeković, T. Pukšec, G. Krajačić, N. Markovska,
V. Borozan, I. Mihaljević, N. Duić

University of Zagreb, Faculty of Mechanical Engineering and Naval Architecture

Macedonian Academy of Arts and Sciences, Skopje, Macedonia

Faculty of Electrical Engineering and Information Technologies, University Sts. Cyril and Methodius,
Skopje, Macedonia

International Centre for Sustainable Development of Energy, Water and Environment Systems,
Zagreb, Croatia

HEP Toplinarstvo d.o.o., Osijek Operative Area Osijek, Croatia

STRATEGO

- IEE project
 - 15 partners from 12 EU countries
- Main goals:
 - Capacity building of local government and DH players
 - Mapping of heating and cooling demand
 - Assistance in the creation of NHCPs



Mapping

- Mapping of useful heating demand
- Identification of priority projects
- Identification of sources of local energy and waste heat
- Assistance with energy planning of cities and regions
- Detailed information for the local government, city planners and the general public


Mapping - Methodology

- Geoportal – location and area of buildings
- Height (number of floors)
- Average energy consumption per type of building





Mapping - Methodology


Matrix (1.36X1.36m)





No. of floors



Type of buildings




Heat map of Osijek
100X100m




Mapping – Future steps

- Calibration
- Linking of public data and data received from the city and DH operator with the map
- Transferring the data to a GIS interface
- Additional layers:
 - Energy certificates
 - Gas and DH grid
 - Waste heat sources...




Thermal Atlas



Peta, The Pan-European Thermal Atlas for Croatia


Disclaimer: The data provided on this website is indicative and for research purposes only. No responsibility is taken for the accuracy of included figures or for using them for unintended purposes.

Choose map



EnergyPLAN

Sustainable Energy
Planning Research
Group, Aalborg
University, Denmark
Deterministic input-
output model
Aggregated
Annual analysis on
an hourly basis
Optimization of the
system



Energy Planning

Thermal PP
Wind
PV
CHP
Hydro
...



Supply



Wind
Solar
Temperature



Meteorological data



Reference model




Validation

Electricity
Heat




Demand



Influence of DH in Osijek


Influence of DH on wind penetration

- Wind penetration increase from 15% to 25% for CEEP < 5%
- At 50% wind power reduction of CEEP from 32% to 20%




Influence of DH on PV penetration

- PV penetration increase from 20% to 30% for CEEP < 5%
- At 50% PV power reduction of CEEP from 26% to 19%



Conclusion

- Advantages of a heat atlas
 - Assistance in planning of heating network development
 - Assessment of DH potential
 - Influence of DH on the overall energy system
 - Increase of intermittent RES penetration
 - Increase of efficiency
 - Reduction of cost and emissions
- 

Acknowledgement

Financial support from the European Union's Intelligent Energy Europe project STRATEGO (grant agreement EE/13/650) is gratefully acknowledged.

Thank you for your attention!
tomislav.novosel@fsb.hr

