



AALBORG UNIVERSITY
DENMARK



District Heating Substation with Electrical Booster Supplied by 40°C Warm District Heating Water

EUDP project - District Heating unit with Electrical Booster for Ultra-Low-Temperature District Heating



Msc. Marek Brand, Ph.D.

marek.brand@danfoss.com

Application Specialist


Danfoss District Energy Application Center



Why reducing the DH supply temperature?

- Improve energy efficiency and better use of renewables
 - Big scale heat pumps -> increase of COP
 - Solar-thermal plants

- Enable use of low-grade waste heat
- Reduce heat loss from DH network
 - Importance increased with reduced demand of buildings



Low-temperature district heating principle


- Temperature levels:

DH supply temperatures		DH network heat loss [%]	Need of on-site heat source
>60°C	Traditional DH	100%	NO
50°C	Low-temperature DH	81%	NO
40°C	Ultra-low-temperature DH	56%	YES

Development
⇒ of new unit

Substation with electrical booster

- DH substation + instantaneous electrical heater (on DHW side)
 - DH designed inlet temperature: 40°C
 - DHW temperature: (37°C) -> 45- 60°C
 - Substation bypass: 40°C
 - DHW output: 24 kW
 - Max. el. power: 11 kW -> 35 A main fuse
- Theoretical share of electricity on
 - DHW : (10°) ⇔ 37°C ⇔ 45°C = 23%
 - (10°) ⇔ 37°C ⇔ 55°C = 40%
- Total heat demand:



Scheme of electrical booster

Building area: 120 m ²	Construction year	Space heating demand [MWh/y]	DHW demand* [MWh/y]	Theoretical share of el. on total heating energy [%] DHW 45°C	Theoretical share of el. on total heating energy [%] DHW 55°C
Low-energy house	2010	6,3	1,8	5,1	8,9
Existing building - newer	1997	16,4	1,8	2,3	4
Existing building - old	1970	20	1,8	1,9	3,3

* Measured in the project


Demonstration area and conditions



- City of Odder
- Five buildings from 1997
- Mainly floor heating + few radiators
- DH network and testing conditions




One of the buildings




Supply temperature **62** El. heater OFF + street bypass 60°C
 Supply temperature **41** El. heater ON + house bypass 40°C

Performance – user perspective

Measuring setup



Performance of electric booster



El. share on DHW part ->

23%

30%

Building area: 120 m ²	Construction year	SH demand [MWh/y]	DHW demand [MWh/y]	Share of el. on total heating energy [%] DHW 45°C	
				Theoretical (23%)	Measured (30%)
Low-energy house	2010	6,3	1,8	5,1%	6,7%
Existing building	1997	16,4	1,8	2,3%	3%
Existing building	1970	20	1,8	1,9%	2,5%

Economy



Reduced heat price can come from:

- Low-grade heat (40°C):
 - Sea water heat pump (sea water cooled from 4°C - 2°C):
 - COP \approx 2.9 for 80/40°C
 - COP \approx 4.2 for 50/30°C => reducing the el input 31 %
 - COP \approx 5.2 for 40/25° => reducing the el input 43 %
 - Use of low-grade waste heat in price level 100 - 332 DKK/MWh
- Return temperature reduction: Biomass CHP reduction 40 \rightarrow 25°C brings 6% lower heat production price
- DH network heat loss reduction

Heat loss "60°C" vs "40°C" (summer conditions)				
DH network supply temperature [°C]	heat loss [MWh/d]	Average supply	Average return	Return temp during idling [°C]
62°C	0,056	61,1	57,5	58
41°C	0,033	42,0	35,5	37
Heat loss reduction [%]	41%			

Example – existing building (1997)



Annual cost [DKK/house/y]				
	benchmark = today 100% DH	variant A (DH price 70%)	variant B (DH price 70% & 50% fuses)	variant C (DH price 70% & el. price 70% & 50% fuses)
Reduced heat loss from DH network	0	-452	-452	-452
Energy bill for DH part	9328	6336	6336	6336
Energy bill for electricity part	0	1156	1156	809
Electric booster unit	0	250	250	250
Installation	0	100	100	100
Fuses - improvement	0	500	250	250
Total	9328	7889	7639	7293
Simple payback time [y]	0,0	11,8	7,1	5,9
<i>Expected lifetime [y]</i>	<i>20</i>	<i>Electrical booster unit [DKK] 5000</i>		
<i>DH original price [DKK/MWh]</i>	<i>512,5</i>	<i>Installation [DKK]</i>		<i>2000</i>
<i>El. original price [DKK/kWh]</i>	<i>2,14</i>	<i>Add 10 A to fuses [DKK]</i>		<i>10000</i>

- Electrical booster enables lower price for district heating through higher heat source efficiencies and reduced heat loss from DH network

Next steps

- Continue with testing and improvements
 - Better el. heater
- More economical analyzes
- Make it as a product
- Find out how long we can run with 40°C supply temperature




Fig. 3. Supply temperature curves for all the investigated cases.

Source: Renewable-based low-temperature district heating for existing buildings in various stages of refurbishment, Brand M, Svendsen S. in Energy 2013, vol. 62, p. 311-319.

Conclusions



- It works, keep high DHW comfort
- Electricity share 2-7% from annual heating energy
- Reasonable payback time also in not “optimal case”
- DHW not as “the requirement” for minimal DH supply temperature
- 40°C supply temperature:
 - Reduced DH heat loss by 50% compared to 80/40/8°C
 - Improves energy efficiency of heat sources
 - Enables low-grade heat sources
- It might be “NEED” for the future DH systems
- Possible to use in both, low-energy but also existing buildings



AALBORG UNIVERSITY
DENMARK



Thank you



Msc. Marek Brand, Ph.D.
marek.brand@danfoss.com
Application Specialist
Danfoss District Energy Application Center

