

Powered by



Innovation Fund Denmark

sEnergies



Funded by the European Union's
Horizon 2020 Research and
Innovation Programme under
Grant Agreement no. 846463



HOFOR



kamstrup

LOGSTOR

Vestas

ENGINEERING
TOMORROW




SOLAR ENERGY IN LOW TEMPERATURE DISTRICT HEATING: MONITORING AND SIMULATION OF AN INNOVATIVE DISTRICT IN MILAN

Dall'Ara D., Dènariè A., Spirito G., Motta M.

Department, Politecnico di Milano



Goals and Motivation



Development of a **digital twin** for Merezzate District




- 1) Fault detection:
 - Verifying monitoring data and improving margins



- 2) Simulating innovative interventions:
 - Converting from HT to LT configuration
 - Evaluation of **decentralised solar system**




Methodology



Merezzate District

 Multi-Dwelling Units (MDU)



Merezzate District



Multi-Dwelling Units (MDU)





Low Energy Buildings




Innovative flat stations

Space heating without HX
DHW without storage tank




TRNSYS System Modelling



TRNSYS System Modelling


5 Multi-dwelling units



TRNSYS System Modelling

5 Multi-dwelling units

22 Buildings




TRNSYS System Modelling

5 Multi-dwelling units

22 Buildings

609 Apartments




TRNSYS System Modelling

5 Multi-dwelling units

22 Buildings

609 Apartments

Primary side



TRNSYS System Modelling


5 Multi-dwelling units

22 Buildings

609 Apartments

Primary side

Secondary side



TRNSYS System Modelling

5 Multi-dwelling units


22 Buildings

609 Apartments

Primary side

Secondary side

Substations



TRNSYS System Modelling

5 Multi-dwelling units

22 Buildings


609 Apartments

Primary side

Secondary side


Substations

Low Temperature



Model Validation & Fault Detection

Model validation:
Q_monitoring




Model Validation & Fault Detection

Model validation:

Q_monitoring

Primary side fault detection

Average difference < **2.30%**



Model Validation & Fault Detection

Model validation:


Q_monitoring

Primary side fault detection

Average difference < **2.30%**

Secondary side fault detection

Average difference < **2.80%**



Model Validation & Fault Detection

Model validation:

Q_monitoring

Primary side fault detection


Average difference < **2.30%**

Secondary side fault detection

Average difference < **2.80%**

Improving margins to reduce

– Temperatures & Mass flows



Decentralised Solar System: High Temperature

Return/return feed-in connection


Most common

Return temperature >

Simple control strategy

Extra pipe needed

100 m² of solar panels for MDU05



Decentralised Solar System: High Temperature

Return/return feed-in connection

Most common


Return temperature >

Simple control strategy

Extra pipe needed

100 m² of solar panels for MDU05

$T > 80\text{ }^{\circ}\text{C} \rightarrow \text{user}$



Decentralised Solar System: High Temperature

Return/return feed-in connection

Most common

Return temperature >


Simple control strategy

Extra pipe needed

100 m² of solar panels for MDU05

$T > 80\text{ }^{\circ}\text{C} \rightarrow \text{user}$

$T < 80\text{ }^{\circ}\text{C} \rightarrow \text{network}$



Decentralised Solar System: High Temperature

Return/return feed-in connection

Most common

Return temperature >

Simple control strategy

Extra pipe needed


100 m² of solar panels for MDU05

$T > 80\text{ °C} \rightarrow \text{user}$

$T < 80\text{ °C} \rightarrow \text{network}$

The solar system can cover:

8.1 % of the annual heating need



Decentralised Solar System: Low Temperature


Return/return feed-in connection

Construction point of view

Solution can remain unchanged

Simplify work on site

100 m² of solar panels for MDU05



Decentralised Solar System: Low Temperature

Return/return feed-in connection


Construction point of view

Solution can remain unchanged

Simplify work on site

100 m² of solar panels for MDU05

$T > 65\text{ }^{\circ}\text{C} \rightarrow \text{user}$



Decentralised Solar System: Low Temperature

Return/return feed-in connection

Construction point of view


Solution can remain unchanged

Simplify work on site

100 m² of solar panels for MDU05

$T > 65\text{ °C} \rightarrow \text{user}$

$T < 65\text{ °C} \rightarrow \text{network}$



Decentralised Solar System: Low Temperature

Return/return feed-in connection

Construction point of view

Solution can remain unchanged

Simplify work on site


100 m² of solar panels for MDU05

$T > 65\text{ °C} \rightarrow \text{user}$


$T < 65\text{ °C} \rightarrow \text{network}$

The solar system can cover:


12.2 % of the annual heating need



Decentralised Solar System: Comparison



LT save **40 MWh** per year




HT save **26 MWh** per year

VS



Conclusion



District heating: **good integration** of centralised and decentralised **renewable sources**

Optimized management



Fundamental step: model validation to understand **reliability of results**



LT network allows to enhance exploitation of **solar gains**

Improve **energy efficiency**



Next steps: analysis of **different solar integrations**

Different feed-in connections

Different management of solar panels



Powered by



Innovation Fund Denmark

sEnergies



Funded by the European Union's
Horizon 2020 Research and
Innovation Programme under
Grant Agreement no. 846463



HOFOR



kamstrup

LOGSTOR

Vestas

ENGINEERING
TOMORROW



THANK YOU FOR YOUR ATTENTION

Dall'Ara D., Dènariè A., Spirito G., Motta M.

Department, Politecnico di Milano

